



Hydro-lution

The evolution of G-Drink never ends. The most successful Glass Front Vendor of our history presented in a new look. A spacious and brightly illuminated showcase enhances the product visibility. New user friendly features offer a large display in blue characters with a new easy door latching system.

DM6

G-Drink Standard DM6 Vertical

TECHNICAL SPECIFICATIONS

	DM6
DIMENSIONS H x W x D (mm)	1830* x 940 x 845
WEIGHT (NET - Standard machine without options)	295 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 5 / Max. 7
NO. OF SELECTIONS	Standard 30 / Max. 42
MAX. CAPACITY (0.33 l CANS)	336
MAX. CAPACITY (0.50 l PET BOTTLES)	240
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +10°C
MAX. POWER CONSUMPTION	800 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	N (+16°C up to +32°C)
ENERGY CONSUMPTION	252 wh/h

* With adjustable leveling screw

The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment

OPTIONAL

- CUSTOMIZED CABINET COLOUR
- SPECIAL CODED LOCK (RIELDA)
- ANTI-VANDALISM KEY PAD AND SAFETY COIN INSERT
- WALL/FLOOR FIXING KIT
- LOCK PROTECTION
- FRONT GLASS PROTECTION
- PRODUCT SPACERS
- VARIOUS FITTING KITS
- BRANDING
- SECURITY CASH BOX SYSTEM
- CO2 COOLING UNIT AVAILABLE